

Supplement

Manual Title: 3PR, 3PG, 180LR, 180LG,
LDR, LDG Safety Information
Part Number: 4808507 Supplement Issue: **2**
Print Date: August 2016 Issue Date: 5/17
Revision/Date: 1, 10/16 Page Count: 1

This supplement contains information necessary
to ensure the accuracy of the above manual.


Change #1, 589, 596, 597

In the **Specifications** section, replace the **Relative Humidity** and the **Safety** sections with:

Relative Humidity	25 % to 80 % (10 °C to 30 °C)
--------------------------	-------------------------------

	3PR, 3PG	180LR, 180LG	LDR, LDG
Safety			
General	IEC 61010-1: Pollution Degree 2		
Laser	IEC 60825-1: Class 3R	IEC 60825-1: Class 2	NA
Max output power	<5 mW	<3 mW	
Wavelength	Red: 635 nm Green: 510 nm		
Laser Beam Divergence	180 ° (π rad), Horizontal and Vertical Beams.		

In the **Symbols** table, replace the laser symbol and description with:

	<p>Indicates a Class 2 laser. DO NOT STARE INTO BEAM The following text may appear with the symbol on the product label: "IEC/EN 60825-1:2014 Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice 50, dated June 24, 2007." In addition, the following pattern on the label will indicate wavelength and optical power: $\lambda = xxxnm, x.xx\text{mW}$.</p>
---	--