

TECHNICAL DATA

Fluke LVD1 Volt Light



Non-contact AC voltage detector and LED flashlight combined in one convenient, compact design, with exclusive dual-sensitivity.

Non-contact AC voltage detector and LED flashlight combined in one convenient, compact design. Exclusive dual-sensitivity provides fast answers in a wide range of situations. The voltage detector glows blue when it's near AC voltage, and glows red when it's at the source. Detects voltages from 40 V AC to 300 V AC. Voltage detector glows blue when sensing 50 Hz - 60 Hz within 2.5 - 13 cm (1 - 5 in) away from source. Ultra-bright white LED with 100,000 hour bulb life. AAA battery included.

Dual levels of detection sensitivity

- Blue indicates you are close to ac voltage
- Red indicates you're at the source
- Detects voltages from 40 V ac to 300 V ac
- Operating Temperature 0 °C to 50 °C
- Ultra-bright white LED
- 100,000 hour bulb
- AAA battery included

SAFETY COMPLIANCE

Meets UL/ANSI 61010-1/CSA22.2
No. 61010-1 (2004) Pollution Degree 2

EMC COMPLIANCE

Meets EN 61326-1:2006,
EN 61326-2-2:2006 CISPR 11

OPERATING

40 V ac to 300 V ac

TEMPERATURE

Operating: 0 °C to 50 °C (32 °F to 122 °F)
Storage: -10 °C to 50 °C (-14 °F to 122 °F)

ALTITUDE

2000 m

CLEANING

Clean with damp cloth

BATTERY LIFE

Approximately 7 hours continuous

WARRANTY

One year





Fluke. *Keeping your world up and running.®*

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

Fluke Europe B.V.

PO Box 1186, 5602 BD
Eindhoven, The Netherlands

For more information call:

In the U.S.A. (800) 443-5853 or

Fax (425) 446-5116

In Europe/M-East/Africa +31 (0) 40 2675 200 or

Fax +31 (0) 40 2675 222

In Canada (800)-36-FLUKE or

Fax (905) 890-6866

From other countries +1 (425) 446-5500 or

Fax +1 (425) 446-5116

Web access: <http://www.fluke.com>

©2005-2015 Fluke Corporation.

Specifications subject to change without notice.

Printed in U.S.A. 10/2015 6006484a-EN

**Modification of this document is not permitted
without written permission from Fluke Corporation.**